



Zippie Xplore 2 - SMD

May 2019

EIPW24



▼ ACCOUNT INFORMATION

Dealer Contact Name: _____	P.O. # or Quote: _____
E-mail Address: _____	
Phone Number: _____ Fax Number: _____	User Name or Number: _____
Bill to (Name): _____	User Weight: _____
Bill to (Location): _____	User Height: _____
Ship to (Name): _____	Seat Cushion Thickness: _____
Address: _____	Knee to Heel Length: Left: _____ Right: _____
City: _____	
Province: _____ Postal Code: _____	

The order cannot be processed without the following:

- A user name or number, the client's measurements and weight
- Sunrise Medical is not responsible for configuration or size discrepancies resulting from customer errors on the order form.
- Order confirmations will be provided by Sunrise Medical summarizing the items selected. Please review this carefully.
- Once the order is shipped, any changes are subject to the returns policy and may be prohibited.

▼ STANDARD OPTIONS

Zippie Power Base, 6-wheel independent wheel suspension, an additional seat suspension system, tie-down hardware for strap systems, 8A offboard charger, 6" front casters on MWD or 8" on RWD, and standard auto style buckle seat positioning strap, 6.5mph motors, **Weight Capacity = 300 lbs.**

► (HYBRID-WHEEL CONFIGURATION) ZIPPIE XPLORE 2 POWER WHEELCHAIR

XPLOREPED2 ZIPPIE XPLORE 2 PED Power Wheelchair

▼ USER WEIGHT PACKAGES


WCA3 300 lbs. Maximum user weight capacity

▼ STANDARD FRAME COLORS

FCBLK Black



▼ OPTIONAL FRAME COLORS (May Increase lead times)



Note 1 Includes matching accessories with the Hydro Graphics option. The matching accessories option is not required with these colours.

▼ TRANSPORT OPTION

TTD4 2 4-Point wheelchair transport brackets

Note 2 4-Point wheelchair transport brackets have not yet received WC-19 crash-testing approval. Use these transport brackets only to secure an unoccupied wheelchair during transport.

▼ MOTOR PACKAGE

MP65 6.5 MPH 4-Pole Motor Package / with COG Release

▼ ASSISTIVE DRIVING PACKAGE

INTELLIDR 3, 4 Intelli-Drive

Note 3 Intelli-Drive technology provides increased tracking capabilities with enhanced traction and steering precision. This is ideal for those with marginal hand function or switch control.

Note 4 Requires the R-net PM 120 Amp Expandable Controller (ECR120)

OTP

▼ BATTERY CHARGER

- BCOB 8A Offboard Battery Charger

▼ BATTERY TRAY AND FRAME SIZE

- FS22B Battery Tray for Group 22NF Batteries (Total frame width = 23 3/8")
 - FS2424B CUSTOM Battery Tray for Group 24 Batteries with a Compact 24" frame width (Mid-Wheel Drive Configuration only) OTP
- Please Select One Option for the Hybrid RWD configuration: Front Caster Arms Flared out (STD) Straight (Optional)
- Note 5** The 23 3/8" compact frame is not compatible with most of the Centermount Front Rigging Options due to Mechanical conflicts.
- Note 6** The 90 degree Power Centermount Elevating & Articulating Foot Platform (ADDPF) is not available with this option.
- Note 7** The Straight Front Arm option is not available with any of the Centermount Front Rigging Options due to Mechanical conflicts.

▼ BATTERIES

- BAT22NFPR GEL Batteries – Group 22NF – (Each-on chair)
- BAT24PR GEL Batteries – Group 24 – (Each-on chair) J

▼ CHOOSE TIRE COLOR (APPLIES TO ALL TIRES OR CASTERS)

- GREY

▼ DRIVE WHEEL

- DW14PT 14" Cast Wheel Pneumatic Tire J
 - DW14PI 14" Cast Wheel Pneumatic with Flat-Free inserts
 - DW144PT 14" x 4" Extra Wide Cast Wheel Pneumatic Tire OTP
 - DW144PI 14" x 4" Extra Wide Cast Wheel Pneumatic with Flat-Free inserts OTP
 - DW12PT 12 1/2" Cast Wheel Pneumatic Tire OTP
 - DW12PI 12 1/2" Cast Wheel Pneumatic with Flat-Free inserts J
- Note 8** The 14" x 4" Extra Wide Wheel increases the overall width of the Base by 2 1/2"
The option to match the wheels to the shroud colour (FC...-M) is not available with the 14" x 4" Extra Wide Wheels.
The 14" x 4" option is not available with the VR2 electronics (ECV902A)
- Note 9** 12 1/2" Drive wheels reduce overall seat to floor height by 1/2", lowers ground clearance and speed, but increases motor torque

▼ FRONT CASTERS (Mid Wheel Configuration)

- FC6S 6" Solid Casters OTP
 - FC8PTM 8" Pneumatic Casters J
 - FC8PIM 8" Pneumatic Casters with Flat-Free inserts
- Note 10** The 8" casters are NOT compatible with the 12 1/2" Drive Wheel configuration (DW12PT and DW12PI)

▼ FRONT CASTERS (Rear-Wheel Hybrid Configuration)

- FC8PTR 8" Pneumatic Casters J
 - FC8PIR 8" Pneumatic Casters with Flat-Free inserts
 - FC9PT 9" Pneumatic Casters OTP
 - FC9PI 9" Pneumatic Casters with Flat-Free inserts OTP
- Note 11** The 9" casters will increase the minimum seat to floor height by 1/2" and are NOT compatible with the 12 1/2" Drive wheel configuration (DW12PT and DW12PI)
The 9" casters are NOT compatible with many front rigging options. Please see details in the front rigging sections

▼ SEAT TO FLOOR HEIGHT (Approximate measurement to the top of seat pan ± 1/4")

► Options for a Seat Only

- | | |
|--|--|
| <input type="checkbox"/> STFH155 12, 13, 15 15 1/2" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1825 13 18 1/4" (Possible Seat angle of 0° and 3°) |
| <input type="checkbox"/> STFH1625 13, 15 16 1/4" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1925 13 19 1/4" (Possible Seat angle of 0°, 3° and 6°) |
| <input type="checkbox"/> STFH1725 13, 15 17 1/4" (Possible Seat angle of 0° and 3°) | <input type="checkbox"/> STFH2025 13 20 1/4" (Possible Seat angle of 0°, 3°, 6°, 9°) |

► Options for a Power Tilt or a STD Power Elevating Seat

- | | |
|--|---|
| <input type="checkbox"/> STFH155 12, 14, 15 15 1/2" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1775 14 17 3/4" (Possible Seat angle of 0° only) |
| <input type="checkbox"/> STFH1625 14, 15 16 1/4" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1825 14 18 1/4" (Possible Seat angle of 0° only) |
| <input type="checkbox"/> STFH1725 14 17 1/4" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1875 14 18 3/4" (Possible Seat angle of 0° only) |

► Options for a Combo - Power Tilt with a STD Power Elevating Seat

- | | |
|--|---|
| <input type="checkbox"/> STFH175 12, 14 17 1/2" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1825 14 18 1/4" (Possible Seat angle of 0° only) |
|--|---|

- Note 12** Requires the 12 1/2" Drive wheels (DW12PT or DW12PI). This lowers ground clearance and speed, but increases motor torque.
- Note 13** Seat to Floor Heights are taken with the Mid-Wheel Drive Configurations. Please remove 1/4" for the Rear-Wheel Drive Height.
- Note 14** Seat to Floor Heights are taken with the Mid-Wheel Drive Configurations. Please Add 1/4" for the Rear-Wheel Drive Height.
- Note 15** The Adult Heavy Duty Swing-Away footrests (SOAAF) are not available with this seat to floor height on the RWD configuration only.

▼ PRE-SET SEAT FRAME ANGLE

- SFE-0 0° Pre-set seat frame seat angle (Must be selected when using power options)
 - SFE-3 3° Pre-set seat frame seat angle (Only available with a seat configuration without power options)
 - SFE-6 6° Pre-set seat frame seat angle (Only available with a seat configuration without power options)
 - SFE-9 9° Pre-set seat frame seat angle (Only available with a seat configuration without power options)
- Note 16** Please refer to the special notes in the above seat to floor height section to confirm seat angle possibilities.
The Light Package is not compatible with the EPSEL option.

▼ NON-EXPANDABLE ELECTRONICS - PG DRIVES VR2 CONTROLLER AND JOYSTICKS

<input type="checkbox"/>	ECV902A	VR2 90 Amp Drive Controller	
<input type="checkbox"/>	ECVJ4K	18 VR2 Standard 4-Key Joystick	
<input type="checkbox"/>	ECVJ6K	18 VR2 6-Key Joystick (Allows for a single power option to operate through this joystick)	
<input type="checkbox"/>	ECVJ9KL	18 VR2 9-Key Joystick with Lighting Operation (Allows for a single power function to operate through this joystick)	OTP
Note 18 Requires the VR2 90A Drive Control (ECV902A) VR2 Electronics can only accommodate a single power seat function The only choices are Power Tilt or Elevating seat			

▼ EXPANDABLE ELECTRONICS - PG DRIVES R-NET CONTROLLERS

<input type="checkbox"/>	ECEL90	R-net EL 90 Amp Expandable Controller	J
<input type="checkbox"/>	ECR120	R-net PM 120 Amp Expandable Controller	OTP
<input type="checkbox"/>	ECRNH	19 Harness for Expandable Controller	
Note 19 Must be ordered with the expandable controller ECEL90 or ECR120 to interface with Joysticks or OMNI screen			

▼ EXPANDABLE ELECTRONICS - PG DRIVES R-NET JOYSTICKS

<input type="checkbox"/>	ECO	Omit Joystick (For use with an OMNI Display)	J
<input type="checkbox"/>	ECELJ	20 R-net (LED) Joystick	J
<input type="checkbox"/>	ECRJJC	20 R-net Joystick with Color screen	J
▶ JOYSTICKS WITH LIGHTING OPERATION			
<input type="checkbox"/>	ECELJL	20 R-net (LED) Joystick with Lighting Operation	OTP
<input type="checkbox"/>	ECRJCL	20 R-net Joystick with Color screen and Lighting Operation	OTP
<input type="checkbox"/>	ECRJCTPL	20 R-net Joystick with Color screen w/ On & Off/ Mode switch & speed pot and Lighting Operation	OTP
▶ ADVANCED JOYSTICK			
<input type="checkbox"/>	ECRJ35	20 R-net Advanced Joystick (3.5" Screen). Lighting Operation, paddle switches, shortcut keys and stereo jacks	OTP
<input type="checkbox"/>	ECRJ35B	20 R-net Advanced Bluetooth Joystick (3.5" Screen). Lighting Operation, paddle switches, shortcut keys and stereo jacks	OTP
Note 20 This option requires the expandable controller ECEL90 or ECR120			

▼ JOYSTICK MOUNT

<input type="checkbox"/>	JSMF	Fixed Joystick Mount	
<input type="checkbox"/>	JMSA	Swing Away Joystick Mount - Height adjustable, Angle adjustable and Multi-Axis	OTP
		<input type="checkbox"/> Set-up with standard installation to swing-away sideways	<input type="checkbox"/> Set-up at 35° to swing-away sideways and downwards
<input type="checkbox"/>	JSMCM	Midline Mounted Swing Away Joystick Mount	OTP

▼ JOYSTICK MOUNT SUPPORT

<input type="checkbox"/>	JSMFH	Joystick mount support Bracket	
--------------------------	-------	--------------------------------	--

▼ JOYSTICK HAND MOUNT

<input type="checkbox"/>	HML	Install Joystick on Left hand side	<input type="checkbox"/>	HMR	Install Joystick on Right hand side
--------------------------	-----	------------------------------------	--------------------------	-----	-------------------------------------

▼ JOYSTICK HANDLE

<input type="checkbox"/>	JSH	Standard Joystick Gimble	
<input type="checkbox"/>	JBAT	Stick Handle 3" in Length	OTP
<input type="checkbox"/>	JBH	Ball Handle	OTP
<input type="checkbox"/>	JFBH	Foam Ball Handle	OTP
<input type="checkbox"/>	JTH	T-Handle	OTP
<input type="checkbox"/>	JMUSH	2.5" Mushroom Handle	OTP
<input type="checkbox"/>	JGP	Goalpost Handle	OTP

▼ ATTENDANT DRIVE CONTROL OPTION

<input type="checkbox"/>	EADC	Attendant Hand Control for R-net EL & PM Controls	OTP
--------------------------	------	---	-----

▼ ATTENDANT JOYSTICK HAND MOUNT

<input type="checkbox"/>	EADCL	Install Attendant Joystick on Rear Left hand side	<input type="checkbox"/>	EADCR	Install Attendant Joystick on Rear Right hand side	OTP
--------------------------	-------	---	--------------------------	-------	--	-----

▼ ENHANCED DISPLAY & DIGITAL INTERFACE BOX (Included with specialty controls)

<input type="checkbox"/>	EDIB	21 OMNI (Enhanced Display & Digital Interface Box with Infrared)	J
Note 21 Allows the switch operation of alternative devices through driver controls. Requires one of the R-net fully Expandable Controllers (ECEL90 or ECR120)			

▼ ENHANCED DISPLAY MOUNT

<input type="checkbox"/>	EDSAM	User Swing Away Mount	<input type="checkbox"/>	EDML (Install Display on LH side)	<input type="checkbox"/>	EDMR (Install Display on RH side)	J
--------------------------	-------	-----------------------	--------------------------	-----------------------------------	--------------------------	-----------------------------------	---

▼ ENVIRONMENTAL CONTROL MODULE

<input type="checkbox"/> ECU	22	Environment control module - (Output Module)	OTP
	Note 22	Requires one of the fully expandable R-net controllers (ECELE90 or ECR120)	

▼ BLUETOOTH MOUSE EMULATOR (Includes USB Dongle)

<input type="checkbox"/> EDBT	23	Bluetooth Mouse Emulator (USB Dongle included)	OTP
	Note 23	Requires one of the fully expandable R-net controllers (ECELE90 or ECR120) . Not required if the ECRJC35B joystick has been selected Not limited to only one selection. Any two can be installed on the same chair, but only one can be used at a time.	
		<input type="checkbox"/> Windows and MAC OS	<input type="checkbox"/> Android Devices
			<input type="checkbox"/> iPhone, iPad and iPod

▼ POWER OPTIONS & SEATING

<input type="checkbox"/> SAABA		Amyseat Rehab Seat - Seat Frame only	
<input type="checkbox"/> SAPTX	24	CG Power Tilt	J
<input type="checkbox"/> SAPRX	24, 25, 26	Power Recline with Integrated Shear Reduction (ISR)	J
<input type="checkbox"/> SAPTPRX	24, 25, 26	CG Power Tilt and Power Recline with Integrated Shear Reduction (ISR)	J
<input type="checkbox"/> SAPESX	24	11" Power Elevating Seat Module for transfer assist	OTP
<input type="checkbox"/> ADDPESX		Module - Add an 11" Power Elevating Seat to either SAPTX, SAPRX or SAPTPRX	OTP
<input type="checkbox"/> ADDMR	25, 26	Module - Manual Recline with Integrated Shear Reduction (ISR)	OTP
	Note 24	These options include the fully adjustable Amyseat (SAABA)	
	Note 25	This option is not available with the Pediatric Seat Frame (SOWN11-16)	
	Note 26	It is recommended to use the Contour Back Support option with the power recline (STDSB or STDSB/CUSTOM).	

▼ ELECTRONICS - SINGLE OR DUAL (1 OR 2 ACTUATORS) POWER SEAT FUNCTION CONTROLLERS

<input type="checkbox"/> EPSV	27, 28	Tilt or Elevating seat activation through 6-key VR2 Hand Control (ECVJ6K or ECVJ9KL)	J
<input type="checkbox"/> EPSEL	27, 28	Tilt or Elevating seat activation through R-NET 90 Amp Expandable Controller (ECELE90)	J
<input type="checkbox"/> SAC		Single (1) Power Seat Function Controller to Interface through R-net Electronics	J
<input type="checkbox"/> DAC		Dual (2) Power Seat Function Controller to Interface through R-net Electronics	J
		With the SAC or DAC, please select one activation and position from the list below	
<input type="checkbox"/> SWTJSS	29, 30	Single actuator activation through R-net Joystick or Specialty Controls EPSR2A	J
<input type="checkbox"/> SWTJSD	29, 31	Dual actuator activation through R-net Joystick or Specialty Controls EPSRA	J
<input type="checkbox"/> SWDUALACT		Dual Activation (Allows to operate all seat functions with external switches and through the joystick)	J
<input type="checkbox"/> SWTOGGLE	30 or 31	Single Toggle Switch (Single Mode: DAC - Dual Mode: SAC)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWPUSH1	30	Single Push Button Switch (Single Mode: SAC)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWPUSH2	30 or 31	Dual Push Button Switch (Single Mode: DAC - Dual Mode: SAC)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
	Note 27	Allows for the activation of a single power option through the VR2 or R-net 90 Amp Controllers. Only the Power Tilt or Elevating seat options are available with this feature.	
	Note 28	These options do not require the SAC controller as they connect via the chair's power module directly	
	Note 29	Requires the R-net 90 Amp (ECELE90) or the 120 Amp (ECR120) Fully Expandable Controllers	
	Note 30	Requires the Single (1 Actuator) Power Seat Function (SAC)	
	Note 31	Requires the Dual (2 Actuators) Power Seat Function (DAC)	

▼ ELECTRONICS - MULTIPLE (3 to 6 ACTUATORS) POWER SEAT FUNCTION CONTROLLER

<input type="checkbox"/> MAC		Multiple (3 to 6 Actuators) Power Seat Function Controller to Interface through R-net Electronics	J
		With the MAC, please select one activation and position from the list below	
<input type="checkbox"/> SWTJSM	32, 33	Multiple Actuator activation through R-net Joystick or Specialty Controls MAC-EPSR	J
<input type="checkbox"/> SWDUALACT		Dual Activation (Allows to operate all seat functions with external switches and through the joystick)	J
<input type="checkbox"/> SWMULTI	32	4-Way Toggle Switch (Up to 4 Activations)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWMULTIT	32	Triple Toggle Switch (Up to 5 Activations)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWPUSH4	32	4-Way Push Button Switch	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWPUSH5	32	5-Way Push Button Switch	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
	Note 32	Requires the Multiple (3 to 6 Actuators) Power Seat Function Controller (MAC)	
	Note 33	Requires the R-net 90 Amp (ECELE90) or 120 Amp (ECR120) Fully Expandable Controller, and the multiple Actuator Controller (MAC)	

▼ SWITCH ACTIVATION HAND MOUNT

Switch Installation: TSML (Install Switch on LH side) TSMR (Install Switch on RH side)

▼ PEDIATRIC ADJUSTABLE SEAT WIDTH RANGE BETWEEN 11" AND 16"

- SOWN11-16 Width adjustment from 11" to 16" with a maximum Depth of 16" (Seat to Floor Height increases by 1/4")
- | | | |
|---------------------------------------|---------------------------------------|---------------------------------------|
| <input type="checkbox"/> 11" (SOWN11) | <input type="checkbox"/> 13" (SOWN13) | <input type="checkbox"/> 15" (SOWN15) |
| <input type="checkbox"/> 12" (SOWN12) | <input type="checkbox"/> 14" (SOWN14) | <input type="checkbox"/> 16" (SOWN16) |

▼ PEDIATRIC ADJUSTABLE SEAT DEPTH RANGE BETWEEN 11" AND 16"

- | | | |
|---------------------------------------|---------------------------------------|---------------------------------------|
| <input type="checkbox"/> 11" (SODN11) | <input type="checkbox"/> 13" (SODN13) | <input type="checkbox"/> 15" (SODN15) |
| <input type="checkbox"/> 12" (SODN12) | <input type="checkbox"/> 14" (SODN14) | <input type="checkbox"/> 16" (SODN16) |

▼ STANDARD ADJUSTABLE SEAT WIDTH RANGE BETWEEN 15" AND 20"

- SOWN15-20-19 (Width adjustment from 15" to 20" with a maximum Depth of 19")
- | | | |
|---------------------------------------|---------------------------------------|--|
| <input type="checkbox"/> 15" (SOWN15) | <input type="checkbox"/> 17" (SOWN17) | <input type="checkbox"/> 19" (SOWN19S) |
| <input type="checkbox"/> 16" (SOWN16) | <input type="checkbox"/> 18" (SOWN18) | <input type="checkbox"/> 20" (SOWN20S) |

▼ ADJUSTABLE SEAT DEPTH RANGE BETWEEN 15" AND 19"

- | | | |
|---------------------------------------|---------------------------------------|---------------------------------------|
| <input type="checkbox"/> 15" (SODN15) | <input type="checkbox"/> 17" (SODN17) | <input type="checkbox"/> 19" (SODN19) |
| <input type="checkbox"/> 16" (SODN16) | <input type="checkbox"/> 18" (SODN18) | |

▼ BACK CANE HEIGHT (The back cane height measurement is taken from the seat pan to the top of the push handles)

- | | | |
|--|--|--|
| <input type="checkbox"/> 16" (SOBCH16) | <input type="checkbox"/> 20" (SOBCH20) | <input type="checkbox"/> 24" (SOBCH24) |
| <input type="checkbox"/> 18" (SOBCH18) | <input type="checkbox"/> 22" (SOBCH22) ³⁴ | <input type="checkbox"/> 26" (SOBCH26) |

Note 34 22" is the minimum back cane height required with a power or manual recline.

▼ PRE-SET SEAT ANGLE (For Non-Reclining Backs)

- SOBAA Please Select one: 86° 90° 94° 98° 102° 106° 110° 114° 118° 122°

▼ BACK SUPPORT

- | | |
|---|-----|
| <input type="checkbox"/> STDSB ³⁵ Standard contour back support 11" to 20" Wide with a maximum shell height of 22" | OTP |
| <input type="checkbox"/> STDSB/CUSTOM Standard contour back support Non Standard Sizes up to 24" wide Width: _____ Depth: _____ | OTP |
| <input type="checkbox"/> Back Rest Upholstery | |
| <input type="checkbox"/> Omit Back Rest Upholstery | |

Note 35 It is recommended to use the Back Support option with the power or manual recline.

▼ BACK SUPPORT TOTAL HEIGHT (MEASURED FROM THE SEAT PAN TO THE TOP OF THE BACK)

- | |
|---|
| <input type="checkbox"/> 16" (SOBH16) |
| <input type="checkbox"/> 18" (SOBH18) |
| <input type="checkbox"/> 20" (SOBH20) |
| <input type="checkbox"/> 22" (SOBH22) ³⁶ |

Note 36 22" is the minimum back height required with a power or manual recline.

Note 37 The space between the bottom of the back and the seat pan is 4" with a non-reclining back and 6" with a reclining back

▼ DUAL POST - HEIGHT ADJUSTABLE ARMRESTS - INCLUDES TRANSFER GRIPS (For Non-Reclining Backs - Choose 2)

- | |
|---|
| <input type="checkbox"/> SOADPPLH Pediatric Dual Post Height Adjustable - Left Side (Height Adjustable from 7 1/4" - 10 1/4") |
| <input type="checkbox"/> SOADPPRH Pediatric Dual Post Height Adjustable - Right Side (Height Adjustable from 7 1/4" - 10 1/4") |
| <input type="checkbox"/> SOADPFLH Dual Post Height Adjustable - Full Length Left Side (Height Adjustable from 10 1/4" - 15 1/4") |
| <input type="checkbox"/> SOADPFRH Dual Post Height Adjustable - Full Length Right Side (Height Adjustable from 10 1/4" - 15 1/4") |
| <input type="checkbox"/> SOADPDLH Dual Post Height Adjustable - Desk Length Left Side (Height Adjustable from 10 1/4" - 15 1/4") |
| <input type="checkbox"/> SOADPDRH Dual Post Height Adjustable - Desk Length Right Side (Height Adjustable from 10 1/4" - 15 1/4") |

▼ RECLINING FLIP-UP, HEIGHT ADJUSTABLE ARMRESTS (For Reclining Backs - Choose 2)

- | | |
|---|----|
| <input type="checkbox"/> SOANIFLH Reclining armrest - Full Length Left Side (Height Adjustable from 10 1/2" to 14" with 1/2" increments) | J* |
| <input type="checkbox"/> SOANIFRH Reclining armrest - Full Length Right Side (Height Adjustable from 10 1/2" to 14" with 1/2" increments) | J* |
| <input type="checkbox"/> SOANIDLH Reclining armrest - Desk Length Left Side (Height Adjustable from 10 1/2" to 14" with 1/2" increments) | J* |
| <input type="checkbox"/> SOANIDRH Reclining armrest - Desk Length Right Side (Height Adjustable from 10 1/2" to 14" with 1/2" increments) | J* |

*Only available with approval for power recline (SMD)

▼ ARMREST HEIGHT ADJUSTMENT AT FACTORY

Please set the Armrest Height at: _____ " (The Armrest Height is taken from the seat pan to the top of the armpad. Not required for Dual Post)

▼ ARMPADS

► Foam Type Selection

<input type="checkbox"/> SOFAPD	Desk Length Standard (10")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	
<input type="checkbox"/> SOFAPF	Full Length Standard (14")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	
<input type="checkbox"/> SOWAPD	39 Desk Length Waterfall (10")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	J
<input type="checkbox"/> SOWAPF	39 Full Length Waterfall (14")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	J

► Hybrid Gel and Foam Type Selection (The Gel always stays soft)

<input type="checkbox"/> SOGELD	Desk Length Hybrid Gel and Foam Flat armpad (10" x 2.5")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP
<input type="checkbox"/> SOGELF	Full Length Hybrid Gel and Foam Flat armpad (14" x 2.5")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP
<input type="checkbox"/> SOWGELD	39 Desk Length Hybrid Gel and Foam Waterfall armpad (10")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP
<input type="checkbox"/> SOWGELF	39 Full Length Hybrid Gel and Foam Waterfall armpad (14")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP

► Specialty Type Selection

<input type="checkbox"/> SOCAR	40 Arm Trough with Hand Support (18" x 4 1/2")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP
	Note 39 The Waterfall armpads may interfere with flipping back the armrests when combined with Lateral Trunk supports			
	Note 40 Arm Trough Armpads may interfere with Armrests Flipping back.			

▼ FOOTRESTS

<input type="checkbox"/> SOPAAF	46 Pediatric Swing-Away Footrests	Set at: <input type="checkbox"/> 60° <input type="checkbox"/> 70° ⁴⁷ <input type="checkbox"/> 80° ^{41, 47} <input type="checkbox"/> 90° ^{41, 47}	<input type="checkbox"/> SOFLP5 (5 1/2" - 7 1/2")	<input type="checkbox"/> SOFLP8 (8 1/2" - 10 1/2")	<input type="checkbox"/> SOFLP10 (10 1/2" - 15 1/2")	
<input type="checkbox"/> SOSAAF	45, 46 Adult Swing-Away Footrests	Set at: <input type="checkbox"/> 60° <input type="checkbox"/> 70° ⁴⁷				
<input type="checkbox"/> SOAAF	45, 46 Adult Heavy Duty Swing-Away footrests	Select Footrest Range: <input type="checkbox"/> SOFLA10 (10 1/2" - 15 1/2") <input type="checkbox"/> SOFLA14 (14 1/2" - 19 1/2")	Set at: <input type="checkbox"/> 60° <input type="checkbox"/> 70° ⁴⁷			J
<input type="checkbox"/> ADDPL	42, 45, 46 Adult Power Elevating & Articulating Legrests	Please Select Function: <input type="checkbox"/> Individual ⁴³ <input type="checkbox"/> Combined ⁴⁴	Select Footrest Range: <input type="checkbox"/> SOFLHD12 (12 1/2" - 15 1/2") <input type="checkbox"/> SOFLHD14 (14 1/2" - 19 1/2")			J*

46 Please set the Footrest Length at: _____ "

*Only available with approval for power ELRs (SMD)

Note 41 Depending on the seat configuration, this option may not be available

Note 42 This option includes calf pads

Note 43 Individual legs count as two power functions.

Note 44 Combined legs count as one power function.

Note 45 This option is not available with the pediatric seat frame (SOWN11-16)

Note 46 The Footrest Length is taken from the top of the seat pan to the top of the footplate. This footrest angle is not compatible with the 9" front casters (FC9PT and FC9PI)

Note 47 This Footrest angle may interfere with the caster when selecting the straight front caster arm option.

▼ FOOTPLATES & ACCESSORIES

<input type="checkbox"/> SOSFAF	Flip-up Footplates			
<input type="checkbox"/> SOAFP	Angle Adjustable & Flip-up Footplates - Pair			J
<input type="checkbox"/> SOAHL	Heel Loops - Pair			
<input type="checkbox"/> SOACPF	Calf Pads for Adult Heavy-Duty Swing-Away footrests (SOAAF) with adjustable hardware - Pair			J

▼ CENTER MOUNTS

<input type="checkbox"/> SOAAF90	50, 51, 52, 55, 56 90° Fixed Center Mount Interface Bracket (Offers Manual adjustability from 95° to 70°)	Select Foot Platform Range: <input type="checkbox"/> SOFBA12 (12 1/2" - 16 1/2") <input type="checkbox"/> SOFBA16 (16 1/2" - 19 1/2")		
<input type="checkbox"/> ADDPF	48, 49, 50, 52, 53, 54, 55 90° Power Center Mount Elevating & Articulating Foot Platform	Select Foot Platform Range: <input type="checkbox"/> SOFBPW12 (12 1/2" - 16 1/2") <input type="checkbox"/> SOFBPW16 (16 1/2" - 20 1/2")		J*

55 Please set the Foot Platform Length at: _____ "

*Only available with approval for power ELRs (SMD)

Note 48 The power center mount counts as one power function

Note 49 This option includes calf pads

Note 50 Links and attaches the one piece center mount foot platform (SOFUFP) or the split footplates (SOAFPF) to the seat

Note 51 With the split footplates option (SOAFPF), this bracket offers independent height adjustability for each footplate

Note 52 Please select the one piece center mount foot platform (SOFUFP) or the split footplates (SOAFPF)

Note 53 This option is not available with the pediatric seat frame (SOWN11-16)

Note 54 This power center mount option is not available with the straight front caster arms (RWD) and Group 24/24 Frame (FS2424B-MWD)

Note 55 The foot platform length is taken from the top of the seat pan to the top of the foot platform or split footplates.

Note 56 This option is not compatible with the 9" Caster option on Rear Hybrid Configuration

▼ FOOT PLATFORMS & ACCESSORIES

<input type="checkbox"/> SOFUFP	Flip-up one piece Foot Platform			
<input type="checkbox"/> SOAFPF	Angle Adjustable & Flip-up Split Footplates for center mount - Each			J
<input type="checkbox"/> SOACPCM	57 Calf Pads for 90° Fixed Center Mount (SOAAF90) with adjustable hardware - Each			J

Note 57 Not available with the pediatric length (SOFBP7 - 7 1/2" - 12 1/2")

▼ SEAT POSITIONING (NOT COMPATIBLE WITH THE WC19 ----- ISO OPTION)

- SOAUTO 55" Seat Positioning Strap

▼ HEADREST

- SONUAHR Using headrest mounting hardware other than SOMAH located below. Specify: _____
- _____ Whitmyer PIL Linx Headrest
- _____ M2300 Bracket

- SOHRBC Bracket to Mount on the Contour Back Support (**Without Recline**)
- SOHRPR Bracket to Mount on the Seat Frame (**For Reclining Backs**)

* Please select one of the headrest options with the mounting hardware and specify where the headrest will be installed



▼ SWITCHES AND OPTIONS

- SSBS Buddy Button Switch OTP
- SSES Egg Switch-Black OTP
- SSML Ultra Light Switch OTP

▼ SPECIALTY DRIVER CONTROL OPTIONS

▼ Therafin Sip-N-Puff Kit

<input type="checkbox"/>	SCSNPK	58, 59	Therafin Sip n' Puff Kit			J
<input type="checkbox"/>	SCSNPBTk	59	Therafin Sip n' Puff Breath Tube Kit			J
<input type="checkbox"/>	SCSRMSNP	59	Stealth Rock-n-Lock Swingaway Arm for Sip-N-Puff	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	J
<input type="checkbox"/>	SCSRM	59	Stealth Rock-n-Lock Swingaway Mount for Mode Switch	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	J
<input type="checkbox"/>	SSES-STD	59, 61	Egg Switch for Changing Modes - Black	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	J
<input type="checkbox"/>	SSBS-STD	59	Buddy Button Switch (Stop Switch) - Red			J
<input type="checkbox"/>	SOMAH	59	Multi-axis Headrest Removable Mounting Hardware			J
<input type="checkbox"/>	SOFHRS	60	Small Curved Headrest Pad 4" x 9"			J
<input type="checkbox"/>	SOFHRM	60	Medium Curved Headrest Pad 5" x 10"			J
<input type="checkbox"/>	SOFHRL	60	Large Curved Headrest Pad 6" x 11"			J

▼ Switch-It Proximity Head Array

<input type="checkbox"/>	SCSIHAA	58, 59	Adult - 3 Switch Proximity Head Array with 1/8" Mono Jack for mode/reverse			OTP
<input type="checkbox"/>	SCSRM	59	Stealth Rock-n-Lock Swingaway Mount for Mode Switch	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	OTP
<input type="checkbox"/>	SSES-STD	59, 61	Egg Switch for Changing Modes - Black	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP
<input type="checkbox"/>	SSBS-STD	59	Buddy Button Switch (Stop Switch) - Red			OTP
<input type="checkbox"/>	SOMAH	59	Multi-axis Headrest Removable Mounting Hardware			OTP

▼ Proportional RIM Head Control Package

<input type="checkbox"/>	SCPHC	58, 59	Proportional RIM Head Control Package			J
<input type="checkbox"/>	SCSRM	59	Stealth Rock-n-Lock Swingaway Mount for Mode Switch	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	J
<input type="checkbox"/>	SSES-STD	59, 61	Egg Switch for Changing Modes - Black	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	J
<input type="checkbox"/>	SOMAH	59	Multi-axis Headrest Removable Mounting Hardware			J

▼ Switch-It MicroPilot Light Touch Proportional Mini joystick for chin / lip control

<input type="checkbox"/>	SCSIMP	58, 59	MicroPilot Light touch mini Proportional Joystick			OTP
<input type="checkbox"/>	SCSRMMP	59	Stealth Rock-n-Lock Swingaway Arm for Chin MP	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	OTP
<input type="checkbox"/>	SCSRM	59	Stealth Rock-n-Lock Swingaway Mount for Mode Switch	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	OTP
<input type="checkbox"/>	SSES-STD	59, 61	Egg Switch for Changing Modes - Black	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP
<input type="checkbox"/>	JCC		Chin Cup			OTP
<input type="checkbox"/>	SOMAH	59	Multi-axis Headrest Removable Mounting Hardware			OTP
<input type="checkbox"/>	SOFHRS	60	Small Curved Headrest Pad 4" x 9"			OTP
<input type="checkbox"/>	SOFHRM	60	Medium Curved Headrest Pad 5" x 10"			OTP
<input type="checkbox"/>	SOFHRL	60	Large Curved Headrest Pad 6" x 11"			OTP

▼ Proportional Compact or Mini joystick for Midline Mount

<input type="checkbox"/>	SCPGMJS	58, 59	PG Drives JC200 Proportional Compact Remote Joystick for Midline Mount			J
<input type="checkbox"/>	SCGMJSM	62	Gatlin Midline Swing-away Mount for JC200	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	J
<input type="checkbox"/>	SCSIMP	58, 59	Switch-It MicroPilot Light touch mini Proportional Joystick			OTP
<input type="checkbox"/>	SCGMPPM	63	Gatlin Midline Swing-away Mount for MicroPilot	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP
<input type="checkbox"/>	SCBTM	64	Bullet Hand Tray for MicroPilot	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP

▼ Proportional Compact or Mini joystick for Armrest Mount

<input type="checkbox"/>	SCPGMJS	58, 59	PG Drives JC200 Proportional Compact Remote Joystick for Armrest Mount			J
<input type="checkbox"/>	SCARMJSM	62	Swing-away and Multi-Axis armrest mount	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	J
<input type="checkbox"/>	SCSIMP	58, 59	Switch-It MicroPilot Light touch mini Proportional Joystick			OTP
<input type="checkbox"/>	SCARMPM	63	Swing-away and Multi-Axis armrest mount	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP
<input type="checkbox"/>	SCBTM	64	Bullet Hand Tray for MicroPilot	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP

- Note 58 Requires the OMNI Enhanced Display and Digital Interface Box (EDIB)
- Note 59 This option must be selected for the kit
- Note 60 Choose one (1) Headrest Pad
- Note 61 The mode switch type can be changed from this selection on Page #7
- Note 62 Must be selected for use with the PG Drives JC200 Mini Joystick
- Note 63 Must be selected for use with the Switch-It MicroPilot
- Note 64 This option is only compatible with the Switch-It MicroPilot

▼ CUSTOM SECTION

Note 65 Lead times will increase depending on the custom order pipeline at the time the purchase order is received. Please call for Quote and specifications for these options.



▼ NOTES / SPECIAL REQUESTS / CUSTOM SPECIFICATIONS
