



Quickie Xperience 2 - SMD

May 2019

EIPW23



▼ ACCOUNT INFORMATION

Dealer Contact Name:	_____	P.O. # or Quote:	_____
E-mail Address:	_____		
Phone Number:	_____	Fax Number:	_____
Bill to (Name):	_____	User Name or Number:	_____
Bill to (Location):	_____	User Weight:	_____
Ship to (Name):	_____	User Height:	_____
Address:	_____	Seat Cushion Thickness:	_____
City:	_____	Knee to Heel Length: Left:	_____
Province:	_____	Right:	_____
	Postal Code:		

The order cannot be processed without the following:

- A user name or number, the client's measurements and weight
- Sunrise Medical is not responsible for configuration or size discrepancies resulting from customer errors on the order form.
- Order confirmations will be provided by Sunrise Medical summarizing the items selected. Please review this carefully.
- Once the order is shipped, any changes are subject to the returns policy and may be prohibited.

▼ STANDARD OPTIONS

Quickie Xperience 2 STD Power Base, 6-wheel independent wheel suspension, an additional seat suspension system, tie-down hardware for strap systems, 8A onboard charger, 6" front casters, and standard auto style buckle seat positioning strap, 6.5 mph motors, **Weight Capacity = 300 lbs.**

▼ QUICKIE XPERIENCE 2 STD POWER WHEELCHAIR

XPERSTD2 QUICKIE XPERIENCE 2 STD Power Wheelchair

▼ USER WEIGHT PACKAGES


WCA3 300 lbs. Maximum user weight capacity

▼ STANDARD FRAME COLORS

FCBLK Black



▼ OPTIONAL FRAME COLORS (May Increase lead times)



Includes matching accessories with the Hydro Graphics Option. The matching accessories option is not required with these colours.

▼ MATCHING ACCESSORIES TO THE FRAME COLOR

FC***-M Matching Accessories to the Frame Color (Wheels, front access door, headrest mount and back shell when selected)
This options is included at no charge with the Hydro Graphics Frame Color option.

▼ TRANSPORT OPTION

TTD4 1 4-Point wheelchair transport brackets

Note 1 4-Point wheelchair transport brackets have not yet received WC-19 crash-testing approval. Use these transport brackets only to secure an unoccupied wheelchair during transport.

▼ MOTOR PACKAGE

MP65 6.5 MPH 4-Pole Motor Package

▼ ASSISTIVE DRIVING PACKAGE

INTELLIDR 2,3 Intelli-Drive

Note 2 Intelli-Drive technology provides increased tracking capabilities with enhanced traction and steering precision. This is ideal for those with marginal hand function or switch control.
Note 3 Requires the R-net PM 120 Amp Expandable Controller (ECR120)

OTP

▼ BATTERY CHARGER

- BCOB 8A Offboard Battery Charger

▼ BATTERY TRAY AND FRAME SIZE

- FS22B Battery Tray for Group 22NF Batteries (Total frame width = 23 3/8")
 - FS24B Battery Tray for Group 24 Batteries (Total frame width = 25 3/8")
 - FS2424B 4 CUSTOM Battery Tray for Group 24 Batteries with a Compact 24" frame width J
OTP
- Note 4 The 90° Power Center Mount Elevating & Articulating Foot Platform (ADDPF) is not available with this option. However, they may be available in certain configurations. Please call CSR for details and possibilities.

▼ BATTERIES

- BAT22NFPR MK Gel Batteries-Group 22NF (Each-On chair)
- BAT24PR MK Gel Batteries-Group 24 (Each-On Chair) J

▼ CHOOSE TIRE COLOR (APPLIES TO ALL TIRES OR CASTERS)

- GREY

▼ DRIVE WHEEL

- DW14PT 14" Cast Wheel Pneumatic Tire J
 - DW14PI 14" Cast Wheel Pneumatic with Flat-free inserts
 - DW144PT 5 14" x 4" Extra Wide Cast Wheel Pneumatic Tire OTP
 - DW144PI 5 14" x 4" Extra Wide Cast Wheel Pneumatic with Flat-free inserts OTP
 - DW12PT 6 12 1/2" Cast Wheel Pneumatic Tire OTP
 - DW12PI 6 12 1/2" Cast Wheel Pneumatic with Flat-free inserts J
- Note 5 The 14" x 4" Extra Wide Wheel increases the overall width of the Base by 2 1/2".
 The option to match the wheels to the shroud colour (FC...M) is not available with the 14" x 4" Extra Wide Wheels.
 The 14" x 4" option is not available with the VR2 electronics (ECV902A)
- Note 6 12 1/2" Drive wheels reduce overall seat to floor height by 1/4", lowers ground clearance and speed, but increases motor torque

▼ FRONT CASTERS

- FC6S 6" Solid Casters (Not available with the 14" x 4" Extra Wide Cast Wheel options DW144PT or DW144PI) OTP
 - FC8PT 7 8" Pneumatic Casters J
 - FC8PI 7 8" Pneumatic Casters with Flat-Free inserts
- Note 7 The 8" casters are NOT compatible with the 12 1/2" Drive wheel configuration (DW12PT and DW12PI)

▼ SEAT TO FLOOR HEIGHT (Approximate measurement to the top of seat pan ± 1/4")

► Options for a Seat Only

- | | |
|--|---|
| <input type="checkbox"/> STFH155 8 15 1/2" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1825 18 1/4" (Possible Seat angle of 0° and 3°) |
| <input type="checkbox"/> STFH1625 16 1/4" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1925 19 1/4" (Possible Seat angle of 0°, 3°, 6°) |
| <input type="checkbox"/> STFH1725 17 1/4" (Possible Seat angle of 0° and 3°) | <input type="checkbox"/> STFH2025 20 1/4" (Possible Seat angle of 0°, 3°, 6°, 9°) |

► Options for a Power Tilt or a STD Power Elevating Seat

- | | |
|---|--|
| <input type="checkbox"/> STFH155 8 15 1/2" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1775 17 3/4" (Possible Seat angle of 0° only) |
| <input type="checkbox"/> STFH1625 16 1/4" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1875 18 3/4" (Possible Seat angle of 0° only) |
| <input type="checkbox"/> STFH1725 17 1/4" (Possible Seat angle of 0° only) | |

► Options for a Combo - Power Tilt with a STD Power Elevating Seat

- | | |
|---|--|
| <input type="checkbox"/> STFH175 8 17 1/2" (Possible Seat angle of 0° only) | <input type="checkbox"/> STFH1825 18 1/4" (Possible Seat angle of 0° only) |
|---|--|

Note 8 Requires the 12 1/2" Drive wheels (DW12PT or DW12PI). This lowers ground clearance and speed, but increases motor torque.

▼ PRE-SET SEAT FRAME ANGLE

- SFE-0 0° Pre-set seat frame seat angle (Must be selected when using power options)
- SFE-3 3° Pre-set seat frame seat angle (Only available with a seat configuration without power options)
- SFE-6 6° Pre-set seat frame seat angle (Only available with a seat configuration without power options)
- SFE-9 9° Pre-set seat frame seat angle (Only available with a seat configuration without power options)

▼ NON-EXPANDABLE ELECTRONICS - PG DRIVES VR2 CONTROLLER AND JOYSTICKS

<input type="checkbox"/>	ECV902A		VR2 90 Amp Drive Controller	
<input type="checkbox"/>	ECVJ4K	10	VR2 Standard 4-Key Joystick	
<input type="checkbox"/>	ECVJ6K	10	VR2 6-Key Joystick (Allows for a single power option to operate through this joystick)	
<input type="checkbox"/>	ECVJ9KL	10	VR2 9-Key Joystick with Lighting Operation (Allows for a single power function to operate through this joystick)	OTP
		Note 10	Requires the VR2 90A Drive Control (ECV902A)	
			VR2 Electronics can only accommodate a single power seat function. The only choices are Power Tilt or Elevating seat	

▼ EXPANDABLE ELECTRONICS - PG DRIVES R-NET CONTROLLERS

<input type="checkbox"/>	ECEL90		R-net EL 90 Amp Expandable Controller	J
<input type="checkbox"/>	ECR120		R-net PM 120 Amp Expandable Controller	OTP
<input type="checkbox"/>	ECRNH	11	Harness for Expandable Controller	
		Note 11	Must be ordered with the expandable controller ECEL90 or ECR120 to interface with Joysticks or OMNI screen	

▼ EXPANDABLE ELECTRONICS - PG DRIVES R-NET JOYSTICKS

<input type="checkbox"/>	ECO		Omit Joystick (For use with an Omni Display)	J
<input type="checkbox"/>	ECELJ	12	R-net (LED) Joystick	J
<input type="checkbox"/>	ECRJJC	12	R-net Joystick with Color screen	J

▶ JOYSTICKS WITH LIGHTING OPERATION

<input type="checkbox"/>	ECELJL	12	R-net (LED) Joystick with Lighting Operation	OTP
<input type="checkbox"/>	ECRJCL	12	R-net Joystick with Color screen and Lighting Operation	OTP

▶ ADVANCED JOYSTICK

<input type="checkbox"/>	ECRJJC35	12	R-net Advanced Joystick (3.5" Screen). Lighting Operation, paddle switches, shortcut keys and stereo jacks	OTP
<input type="checkbox"/>	ECRJJC35B	12	R-net Advanced Bluetooth Joystick (3.5" Screen). Lighting Operation, paddle switches, shortcut keys and stereo jacks	OTP
		Note 12	This option requires the expandable controller ECEL90 or ECR120	

▼ JOYSTICK MOUNT

<input type="checkbox"/>	JSMF		Fixed Joystick Mount	
<input type="checkbox"/>	JSMSA		Swing Away Joystick Mount - Height adjustable, Angle adjustable and Multi-Axis	OTP
			<input type="checkbox"/> Set-up with standard installation to swing-away sideways <input type="checkbox"/> Set-up at 35° to swing-away sideways and downwards	
<input type="checkbox"/>	JSMCM		Midline Mounted Swing Away Joystick Mount	OTP

▼ JOYSTICK MOUNT SUPPORT

<input type="checkbox"/>	JSMFH		Joystick mount support Bracket	
--------------------------	-------	--	--------------------------------	--

▼ JOYSTICK HAND MOUNT

<input type="checkbox"/>	HML	Install Joystick on Left hand side	<input type="checkbox"/>	HMR	Install Joystick on Right hand side
--------------------------	-----	------------------------------------	--------------------------	-----	-------------------------------------

▼ JOYSTICK HANDLE

<input type="checkbox"/>	JSH		Standard Joystick Gimble	
<input type="checkbox"/>	JBAT		Stick Handle 3" in Length	OTP
<input type="checkbox"/>	JBH		Ball Handle	OTP
<input type="checkbox"/>	JFBH		Foam Ball Handle	OTP
<input type="checkbox"/>	JTH		T-Handle	OTP
<input type="checkbox"/>	JMUSH	New	2.5" Mushroom Handle	OTP
<input type="checkbox"/>	JGP		Goalpost Handle	OTP

▼ ATTENDANT DRIVE CONTROL OPTION

<input type="checkbox"/>	EADC		Attendant Hand Control for R-net EL & PM Controls	OTP
--------------------------	------	--	---	-----

▼ ATTENDANT JOYSTICK HAND MOUNT

<input type="checkbox"/>	EADCL	Install Attendant Joystick on Rear Left hand side	<input type="checkbox"/>	EADCR	Install Attendant Joystick on Rear Right hand side
--------------------------	-------	---	--------------------------	-------	--

▼ ENHANCED DISPLAY & DIGITAL INTERFACE BOX (Included with specialty controls)

<input type="checkbox"/>	EDIB	13	OMNI (Enhanced Display & Digital Interface Box with Infrared)	J
		Note 13	Allows the switch operation of alternative devices through driver controls. Requires one of the R-net fully Expandable Controllers (ECEL90 or ECR120)	

▼ ENHANCED DISPLAY MOUNT

<input type="checkbox"/>	EDSAM		User Swing Away Mount	<input type="checkbox"/>	EDML (Install Display on LH side)	<input type="checkbox"/>	EDMR (Install Display on RH side)	J
--------------------------	-------	--	-----------------------	--------------------------	-----------------------------------	--------------------------	-----------------------------------	---

▼ ENVIRONMENTAL CONTROL MODULE

<input type="checkbox"/> ECU	14	Environment control module - (Output Module)	OTP
Note 14		Requires one of the fully expandable R-net controllers (ECEL90 or ECR120)	

▼ BLUETOOTH MOUSE EMULATOR (Includes USB Dongle)

<input type="checkbox"/> EDBT	15	Bluetooth Mouse Emulator (USB Dongle included)	OTP
Note 15		Requires one of the fully expandable R-net controllers (ECEL90 or ECR120) . Not required if the ECRJC35B joystick has been selected Not limited to only one selection. Any two can be installed on the same chair, but only one can be used at a time.	
		<input type="checkbox"/> Windows and MAC OS	<input type="checkbox"/> Android Devices
			<input type="checkbox"/> iPhone, iPad and iPod

▼ POWER OPTIONS & SEATING

<input type="checkbox"/> SAABA		Amyseat Rehab Seat - Seat Frame only	
<input type="checkbox"/> SAPTX	16	CG Power Tilt	J
<input type="checkbox"/> SAPRX	16, 18	Power Recline with Integrated Shear Reduction (ISR)	J
<input type="checkbox"/> SAPTPRX	16, 18	CG Power Tilt and Power Recline with Integrated Shear Reduction (ISR)	J
<input type="checkbox"/> SAPESX	16	11" Power Elevating Seat Module for transfer assist	OTP
<input type="checkbox"/> ADDPESX		Module - Add an 11" Power Elevating Seat to either SAPTX, SAPRX or SAPTPRX	OTP
<input type="checkbox"/> ADDMR	17, 18	Module - Manual Recline with Integrated Shear Reduction (ISR)	OTP
Note 16		These options include the fully adjustable Amyseat (SAABA)	
Note 17		The maximum user weight capacity with this option is 250 lbs	
Note 18		It is recommended to use the Contour Back Support option with the power or manual reclines (STDSB or STDSB/CUSTOM)	

▼ ELECTRONICS - SINGLE OR DUAL (1 OR 2 ACTUATORS) POWER SEAT FUNCTION CONTROLLERS

<input type="checkbox"/> EPSV	19, 20	Tilt or Elevating seat activation through 6-key VR2 Hand Control (ECVJ6K or ECVJ9KL)	J
<input type="checkbox"/> EPSEL	19, 20	Tilt or Elevating seat activation through RNET 90 Amp Expandable Controller (ECEL90)	J
<input type="checkbox"/> SAC		Single (1) Power Seat Function Controller to Interface through R-net Electronics	J
<input type="checkbox"/> DAC		Dual (2) Power Seat Function Controller to Interface through R-net Electronics	J
With the SAC or DAC, please select one activation and position from the list below			
<input type="checkbox"/> SWTJSS	21, 22	Single actuator activation through R-net Joystick or Specialty Controls EPSR2A	J
<input type="checkbox"/> SWTJSD	21, 23	Dual actuator activation through R-net Joystick or Specialty Controls EPSRA	J
<input type="checkbox"/> SWDUALACT		Dual Activation (Allows to operate all seat functions with external switches and through the joystick)	J
<input type="checkbox"/> SWTOGGLE	22 or 23	Single Toggle Switch (Single Mode: DAC - Dual Mode: SAC)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWPUSH1	22	Single Push Button Switch (Single Mode: SAC)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWPUSH2	22 or 23	Dual Push Button Switch (Single Mode: DAC - Dual Mode: SAC)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
Note 19 Allows for the activation of a single power option through the VR2 or R-net 90 Amp Controllers. Only the Power Tilt or Elevating seat options are available with this feature.			
Note 20 These options do not require the SAC controller as they connect via the chair's power module directly			
Note 21 Requires the R-net 90 Amp (ECEL90) or the 120 Amp (ECR120) Fully Expandable Controllers			
Note 22 Requires the Single (1 Actuator) Power Seat Function (SAC)			
Note 23 Requires the Dual (2 Actuators) Power Seat Function (DAC)			

▼ ELECTRONICS - MULTIPLE (3 to 6 ACTUATORS) POWER SEAT FUNCTION CONTROLLER

<input type="checkbox"/> MAC		Multiple (3 to 6 Actuators) Power Seat Function Controller to Interface through R-net Electronics	J
With the MAC, please select one activation and position from the list below			
<input type="checkbox"/> SWTJSM	24, 25	Multiple Actuator activation through R-net Joystick or Specialty Controls MAC-EPSR	J
<input type="checkbox"/> SWDUALACT		Dual Activation (Allows to operate all seat functions with external switches and through the joystick)	J
<input type="checkbox"/> SWMULTI	25	4-Way Toggle Switch (Up to 4 Activations)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWMULTIT	25	Triple Toggle Switch (Up to 5 Activations)	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWPUSH4	25	4-Way Push Button Switch	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
<input type="checkbox"/> SWPUSH5	25	5-Way Push Button Switch	<input type="checkbox"/> User Activation <input type="checkbox"/> Attendant Activation
Note 24 Requires the Multiple (3 to 6 Actuators) Power Seat Function Controller (MAC)			
Note 25 Requires the R-net 90 Amp (ECEL90) or 120 Amp (ECR120) Fully Expandable Controller, and the multiple Actuator Controller (MAC)			

▼ SWITCH ACTIVATION HAND MOUNT

Switch Installation: TSML (Install Switch on LH side) TSMR (Install Switch on RH side)

▼ PRE-SET SEAT ANGLE (For Non-Reclining Backs)

SOBAA Please Select one: 86° 90° 94° 98° 102° 106° 110° 114° 118° 122°

▼ STANDARD ADJUSTABLE SEAT WIDTH RANGE BETWEEN 15" AND 20"

- SOWN15-20-19 (Width adjustment from 15" to 20" with a maximum Depth of 19")
 - SOWN15-20-22 (Width adjustment from 15" to 20" with a maximum Depth of 22")
-
- | | | |
|---------------------------------------|---------------------------------------|--|
| <input type="checkbox"/> 15" (SOWN15) | <input type="checkbox"/> 17" (SOWN17) | <input type="checkbox"/> 19" (SOWN19S) |
| <input type="checkbox"/> 16" (SOWN16) | <input type="checkbox"/> 18" (SOWN18) | <input type="checkbox"/> 20" (SOWN20S) |

▼ LARGE ADJUSTABLE SEAT WIDTH RANGE BETWEEN 19" AND 24"

- SOWN19-24-22 (Width adjustment from 19" to 24" and Depth range of 18" to 22")
-
- | | | |
|--|---------------------------------------|---------------------------------------|
| <input type="checkbox"/> 19" (SOWN19L) | <input type="checkbox"/> 21" (SOWN21) | <input type="checkbox"/> 23" (SOWN23) |
| <input type="checkbox"/> 20" (SOWN20L) | <input type="checkbox"/> 22" (SOWN22) | <input type="checkbox"/> 24" (SOWN24) |

▼ ADJUSTABLE SEAT DEPTH RANGE BETWEEN 15" AND 22"

- | | | | |
|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| <input type="checkbox"/> 15" (SODN15) | <input type="checkbox"/> 16" (SODN16) | <input type="checkbox"/> 17" (SODN17) | <input type="checkbox"/> 18" (SODN18) |
| <input type="checkbox"/> 19" (SODN19) | <input type="checkbox"/> 20" (SODN20) | <input type="checkbox"/> 21" (SODN21) | <input type="checkbox"/> 22" (SODN22) |

▼ BACK CANE HEIGHT (The back cane height measurement is taken from the seat pan to the top of the push handles)

- | | | |
|--|--|--|
| <input type="checkbox"/> 16" (SOBCH16) | <input type="checkbox"/> 20" (SOBCH20) | <input type="checkbox"/> 24" (SOBCH24) |
| <input type="checkbox"/> 18" (SOBCH18) | <input type="checkbox"/> 22" (SOBCH22) ²⁶ | <input type="checkbox"/> 26" (SOBCH26) |

Note 26 22" is the minimum back cane height required with a power or manual recline.

▼ BACK SUPPORT

- | | | |
|--|--|----------------------------------|
| <input type="checkbox"/> STDSB ²⁷ | Standard contour back support 15" to 20" Wide with a maximum shell height of 22" | OTP |
| <input type="checkbox"/> STDSB/CUSTOM | Standard contour back support Non Standard Sizes up to 24" wide | Width: _____ Depth: _____
OTP |
| <input type="checkbox"/> Back Rest Upholstery | | |
| <input type="checkbox"/> Omit Back Rest Upholstery | | |

Note 27 It is recommended to use the Back Support option with the power or manual recline.

▼ BACK SUPPORT TOTAL HEIGHT (MEASURED FROM THE SEAT PAN TO THE TOP OF THE BACK)

- | | |
|---------------------------------------|---|
| <input type="checkbox"/> 16" (SOBH16) | <input type="checkbox"/> 20" (SOBH20) |
| <input type="checkbox"/> 18" (SOBH18) | <input type="checkbox"/> 22" (SOBH22) ²⁸ |

Note 28 22" is the minimum back height required with a power or manual recline.

Note 29 The space between the bottom of the back and the seat pan is 4" with a non-reclining back and 6" with a reclining back

▼ DUAL POST - HEIGHT ADJUSTABLE ARMRESTS - INCLUDES TRANSFER GRIPS (For Non-Reclining Backs - Choose 2)

- | | |
|-----------------------------------|---|
| <input type="checkbox"/> SOADPFLH | Dual Post Height Adjustable - Full Length Left Side (Height Adjustable from 10 ¼" - 15 ¼") |
| <input type="checkbox"/> SOADPFRH | Dual Post Height Adjustable - Full Length Right Side (Height Adjustable from 10 ¼" - 15 ¼") |
| <input type="checkbox"/> SOADPDLH | Dual Post Height Adjustable - Desk Length Left Side (Height Adjustable from 10 ¼" - 15 ¼") |
| <input type="checkbox"/> SOADPDRH | Dual Post Height Adjustable - Desk Length Right Side (Height Adjustable from 10 ¼" - 15 ¼") |

▼ RECLINING FLIP-UP, HEIGHT ADJUSTABLE ARMRESTS (For Reclining Backs - Choose 2)

- | | | |
|-----------------------------------|---|----|
| <input type="checkbox"/> SOANIFLH | Reclining armrest - Full Length Left Side (Height Adjustable from 10 ½" to 14" with ½" increments) | J* |
| <input type="checkbox"/> SOANIFRH | Reclining armrest - Full Length Right Side (Height Adjustable from 10 ½" to 14" with ½" increments) | J* |
| <input type="checkbox"/> SOANIDLH | Reclining armrest - Desk Length Left Side (Height Adjustable from 10 ½" to 14" with ½" increments) | J* |
| <input type="checkbox"/> SOANIDRH | Reclining armrest - Desk Length Right Side (Height Adjustable from 10 ½" to 14" with ½" increments) | J* |

*Only available with approval for power recline (SMD)

▼ ARMREST HEIGHT ADJUSTMENT AT FACTORY

Please set the Armrest Height at: _____ " (The Armrest Height is taken from the seat pan to the top of the armpad. Not required for Dual Post)

▼ ARMPADS

► Foam Type Selection

<input type="checkbox"/> SOFAPD	Desk Length Standard (10")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	
<input type="checkbox"/> SOFAPF	Full Length Standard (14")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	
<input type="checkbox"/> SOWAPD	30 Desk Length Waterfall (10")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	J
<input type="checkbox"/> SOWAPF	30 Full Length Waterfall (14")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	J

► Hybrid Gel and Foam Type Selection (The Gel always stays soft)

<input type="checkbox"/> SOGELD	Desk Length Hybrid Gel and Foam Flat armpad (10" x 2.5")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP
<input type="checkbox"/> SOGELF	Full Length Hybrid Gel and Foam Flat armpad (14" x 2.5")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP
<input type="checkbox"/> SOWGELD	30 Desk Length Hybrid Gel and Foam Waterfall armpad (10")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP
<input type="checkbox"/> SOWGELF	30 Full Length Hybrid Gel and Foam Waterfall armpad (14")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP

► Specialty Type Selection

<input type="checkbox"/> SOCAR	31 Arm Trough with Hand Support (18" x 4 1/2")	Select Side: <input type="checkbox"/> Left Hand Side	<input type="checkbox"/> Right Hand Side	OTP
--------------------------------	--	--	--	-----

Note 30 The Waterfall armpads may interfere with flipping back the armrests when combined with Lateral Trunk supports
Note 31 Arm Trough Armpads may interfere with Armrests Flipping back.

▼ FOOTRESTS

<input type="checkbox"/> SOSAAF	35 Adult Swing-Away Footrests	Set at: <input type="checkbox"/> 60°	<input type="checkbox"/> 70°	
		Select Footrest Range: <input type="checkbox"/> SOFLA10 (10 1/2" - 15 1/2")	<input type="checkbox"/> SOFLA14 (14 1/2" - 19 1/2")	
<input type="checkbox"/> SOAAF	35 Adult Heavy Duty Swing-Away footrests	Set at: <input type="checkbox"/> 60°	<input type="checkbox"/> 70°	
		Select Footrest Range: <input type="checkbox"/> SOFLHD12 (12 1/2" - 15 1/2")	<input type="checkbox"/> SOFLHD14 (14 1/2" - 19 1/2")	
<input type="checkbox"/> ADDPL	32, 35 Adult Power Elevating & Articulating Legrests	Please Select Function: <input type="checkbox"/> Individual ³³	<input type="checkbox"/> Combined ³⁴	
		Select Footrest Range: <input type="checkbox"/> SOFLPW12 (12 1/2" - 15 1/2")	<input type="checkbox"/> SOFLPW14 (14 1/2" - 19 1/2")	J*

35 Please set the Footrest Length at: _____ " *Only available with approval for power ELRs (SMD)

Note 32 This options includes calf pads
Note 33 Individual legs count as two power functions.
Note 34 Combined legs count as one power function.
Note 35 The Footrest Length is taken from the top of the seat pan to the top of the footplate.

▼ FOOTPLATES & ACCESSORIES

<input type="checkbox"/> SOSFAF	Flip-up Footplates			
<input type="checkbox"/> SOAFP	Angle Adjustable & Flip-up Footplates - Pair			J
<input type="checkbox"/> SOAHL	Heel Loops - Pair			
<input type="checkbox"/> SOACPFR	Calf Pads for Adult Heavy-Duty Swing-Away footrests (SOAAF) with adjustable hardware - Pair			J

▼ CENTER MOUNTS

<input type="checkbox"/> SOAAF90	38, 39, 40 90° Fixed Center Mount Interface Bracket (Offers Manual adjustability from 95° to 70°)	Select Foot Platform Range: <input type="checkbox"/> SOFBA12 (12 1/2" - 16 1/2")	<input type="checkbox"/> SOFBA16 (16 1/2" - 19 1/2")	
<input type="checkbox"/> ADDPF	36, 37, 38, 39, 40 90° Power Center Mount Elevating & Articulating Foot Platform	Select Foot Platform Range: <input type="checkbox"/> SOFBPW12 (12 1/2" - 16 1/2")	<input type="checkbox"/> SOFBPW16 (16 1/2" - 20 1/2")	J*

Please set the Foot Platform Length at: _____ " *Only available with approval for power ELRs (SMD)

Note 36 The power centermount counts as one power function
Note 37 This option includes calf pads
Note 38 Links and attaches the one piece center mount foot platform (SOFUPF) or the split footplates (SOAFPFB) to the seat
Note 39 Please select the one piece centermount foot platform (SOFUPF) or the split footplates (SOAFPFB)
Note 40 The Foot Platform length is taken from the top of the seat pan to the top of the foot platform or split footplates.
 Centermount Front Riggings are not available with the Straight Front Arm option due to Mechanical conflicts.
 This option is not compatible with the 9" Caster option.

▼ FOOT PLATFORMS & ACCESSORIES

<input type="checkbox"/> SOFUPF	Flip-up one piece Foot Platform			
<input type="checkbox"/> SOAFPFB	Angle Adjustable & Flip-up Split Footplates for center mount - Each			J
<input type="checkbox"/> SOACPFCM	Calf Pads for 90° Fixed Center Mount (SOAAF90) with adjustable hardware - Each			J

▼ SEAT POSITIONING (NOT COMPATIBLE WITH THE WC19-ISO OPTION)

SOAUTO 55" Seat Positioning Strap

▼ HEADREST

SONUAHR Using headrest mounting hardware other than SOMAH located below. Specify: _____

_____ Whitmyer PIL Linx Headrest

_____ M2300 Bracket

SOHRSB Bracket to Mount on the Seat Frame crossbar (**Without Recline**)

SOHRPR Bracket to Mount on the Seat Frame (**For Reclining Backs**)

Please select one of the headrest options with the mounting hardware and specify where the headrest will be installed (The frame or back cushion)

▼ SWITCHES AND OPTIONS

SSBS-STD Buddy Button Switch OTP

SSES-STD Egg Switch-Black OTP

SSML Ultra Light Switch OTP

▼ SPECIALTY DRIVER CONTROL OPTIONS

▼ Therafin Sip n' Puff Kit

<input type="checkbox"/>	SCSNPK	41,42	Therafin Sip n' Puff Kit			J
<input type="checkbox"/>	SCSNPBTK	42	Therafin Sip n' Puff Breath Tube Kit			J
<input type="checkbox"/>	SCSRMSNP	42	Stealth Rock-n-Lock Swingaway Arm for Sip-N-Puff	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	J
<input type="checkbox"/>	SCSRM	42	Stealth Rock-n-Lock Swingaway Mount for Mode Switch	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	J
<input type="checkbox"/>	SSES-STD	42,44	Egg Switch for Changing Modes - Black	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	J
<input type="checkbox"/>	SSBS-STD	42	Buddy Button Switch (Stop Switch) - Red			J
<input type="checkbox"/>	SOMAH	42	Multi-axis Headrest Removable Mounting Hardware			J
<input type="checkbox"/>	SOFHRS	43	Small Curved Headrest Pad 4" x 9"			J
<input type="checkbox"/>	SOFHRM	43	Medium Curved Headrest Pad 5" x 10"			J
<input type="checkbox"/>	SOFHRL	43	Large Curved Headrest Pad 6" x 11"			J

▼ Switch-It Proximity Head Array

<input type="checkbox"/>	SCSIHAA	41,42	Adult - 3 Switch Proximity Head Array with 1/8" Mono Jack for mode/reverse			OTP
<input type="checkbox"/>	SCSRM	42	Stealth Rock-n-Lock Swingaway Mount for Mode Switch	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	OTP
<input type="checkbox"/>	SSES-STD	42,44	Egg Switch for Changing Modes - Black	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP
<input type="checkbox"/>	SSBS-STD	42	Buddy Button Switch (Stop Switch) - Red			OTP
<input type="checkbox"/>	SOMAH	42	Multi-axis Headrest Removable Mounting Hardware			OTP

▼ Switch-It Proximity Head Array & Sip-N-Puff Combo

<input type="checkbox"/>	SCSICMBOA	41,42	Adult-4 Switch Combo Head Array with two proximity sensors for Left & Right and Low pressure Sip n' Puff for forward and reverse and 1/8"			OTP
<input type="checkbox"/>	SCSNPBTK	42	Therafin Sip n' Puff Breath Tube Kit			OTP
<input type="checkbox"/>	SCSRMSNP	42	Stealth Rock-n-Lock Swingaway Arm for Sip-N-Puff	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	OTP
<input type="checkbox"/>	SCSRM	42	Stealth Rock-n-Lock Swingaway Mount for Mode Switch	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	OTP
<input type="checkbox"/>	SSES-STD	42,44	Egg Switch for Changing Modes - Black	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP
<input type="checkbox"/>	SSBS-STD	42	Buddy Button Switch (Stop Switch) - Red			OTP
<input type="checkbox"/>	SOMAH	42	Multi-axis Headrest Removable Mounting Hardware			OTP

▼ Proportional RIM Head Control Package

<input type="checkbox"/>	SCPHC	41,42	Proportional RIM Head Control Package			J
<input type="checkbox"/>	SCSRM	42	Stealth Rock-n-Lock Swingaway Mount for Mode Switch	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	J
<input type="checkbox"/>	SSES-STD	42,44	Egg Switch for Changing Modes - Black	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	J
<input type="checkbox"/>	SOMAH	42	Multi-axis Headrest Removable Mounting Hardware			J

▼ Switch-It MicroPilot Light Touch Proportional Mini joystick for chin / lip control

<input type="checkbox"/>	SCSIMP	41,42	MicroPilot Light touch mini Proportional Joystick			OTP
<input type="checkbox"/>	SCSRMMP	42	Stealth Rock-n-Lock Swingaway Arm for Chin MP	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	OTP
<input type="checkbox"/>	SCSRM	42	Stealth Rock-n-Lock Swingaway Mount for Mode Switch	<input type="checkbox"/> SWL (Swings on Left)	<input type="checkbox"/> SWR (Swings on Right)	OTP
<input type="checkbox"/>	SSES-STD	42,44	Egg Switch for Changing Modes - Black	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP
<input type="checkbox"/>	JCC		Chin Cup			OTP
<input type="checkbox"/>	SOMAH	42	Multi-axis Headrest Removable Mounting Hardware			OTP
<input type="checkbox"/>	SOFHRS	43	Small Curved Headrest Pad 4" x 9"			OTP
<input type="checkbox"/>	SOFHRM	43	Medium Curved Headrest Pad 5" x 10"			OTP
<input type="checkbox"/>	SOFHRL	43	Large Curved Headrest Pad 6" x 11"			OTP

▼ Proportional Compact or Mini joystick for Midline Mount

<input type="checkbox"/>	SCPGMJS	41,42	PG Drives JC200 Proportional Compact Remote Joystick for Midline Mount			J
<input type="checkbox"/>	SCGMJSM	45	Gatlin Midline Swing-away Mount for JC200	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	J
<input type="checkbox"/>	SCSIMP	41,42	Switch-It MicroPilot Light touch mini Proportional Joystick			OTP
<input type="checkbox"/>	SCGMPM	46	Gatlin Midline Swing-away Mount for MicroPilot	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP
<input type="checkbox"/>	SCBTM	47	Bullet Hand Tray for MicroPilot	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP

▼ Proportional Compact or Mini joystick for Armrest Mount

<input type="checkbox"/>	SCPGMJS	41,42	PG Drives JC200 Proportional Compact Remote Joystick for Armrest Mount			J
<input type="checkbox"/>	SCARMJSM	45	Swing-away and Multi-Axis armrest mount	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	J
<input type="checkbox"/>	SCSIMP	41,42	Switch-It MicroPilot Light touch mini Proportional Joystick			OTP
<input type="checkbox"/>	SCARMJSM	46	Swing-away and Multi-Axis armrest mount	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP
<input type="checkbox"/>	SCBTM	47	Bullet Hand Tray for MicroPilot	<input type="checkbox"/> MLH (Mount on Left)	<input type="checkbox"/> MRH (Mount on Right)	OTP

Note 41 Requires the OMNI Enhanced Display and Digital Interface Box (EDIB)

Note 42 This option must be selected for the kit

Note 43 Choose one (1) Headrest Pad

Note 44 The mode switch type can be changed from this selection on Page #6


Note 45 Must be selected for use with the PG Drives JC200 Mini Joystick

Note 46 Must be selected for use with the Switch-It MicroPilot

Note 47 This option is only compatible with the Switch-It MicroPilot

▼ CUSTOM SECTION

Note 48 Lead times will increase depending on the custom order pipeline at the time the purchase order is received. Please call for Quote and specifications for these options.



▼ NOTES / SPECIAL REQUESTS / CUSTOM SPECIFICATIONS
