

Sunrise/MWP Manual Wheelchair Specification Form Quickie® GP Swing Away

February 2014

CUSTOMER INFORMATION

ACCOUNT #: _____ SHIP TO: _____
 DATE: _____ NAME: _____
 P.O.#: _____ ADDRESS: _____
 CITY: _____ PROVINCE: _____
 POSTAL CODE: _____ PHONE NUMBER: _____
 BUYER: _____ MARKED FOR: _____



QUICKIE GP SWING AWAY

025WM26 **WMA4QU005** Quickie GP Swing Away \$2,845.00
 Max. User Weight: 250 lbs

FRAME COLOR

025C2 Black NC

FRAME WIDTH¹

025W3 12"² NC
 025W4 13"² NC
 025W5 14" NC
 025W6 15" NC
 025W7 16" NC
 025W8 17" NC
 025W9 18" NC
 025W10 **WAMA** 19" \$255.00
 025W11 **WAMA** 20" \$255.00

SLING DEPTH

025SD5 12" NC
 025SD6 13" NC
 025SD7 14" NC
 025SD8 15" NC
 025SD9 16" NC
 025SD10 17" NC
 025SD11 18" NC
 025SD12 **WAMB** 19" \$255.00
 025SD13 **WAMB** 20" \$255.00
 025SD14 **WAMB** 21" \$255.00
 025SD33 **WAMB** 22" \$255.00

FRONT SEAT HEIGHT

Enter Front Seat Height _____

REAR SEAT HEIGHT

Enter Rear Seat Height _____

BACK TYPE

025BT1 Folding Adjustable
 025BA1 11"-14" \$100.00
 025BA2 12"-16" \$100.00
 025BA3 14"-18" \$100.00
 025BA4 16"-20" \$100.00
 025BT3 Non-Folding Backrest ^{4,5} NC
 025BB1 8" NC
 025BB2 9" NC
 025BB3 10" NC
 025BB4 11" NC
 025BB5 12" NC
 025BB6 13" NC
 025BB7 14" NC
 025BB8 15" NC
 025BB9 16" NC

BACK UPHOLSTERY

025BU1 Standard NC
 025BU8 **WAMD/WAME** Adjustable ⁷ \$170.00 (1)
 025BU16 Reinforced ⁴ \$45.00 (1)
 025BU14 Omit Upholstery -\$18.00

BACKREST OPTIONS

025BT33 Folding w/Integral Push Handles NC
 025A85 Bolt-On Push Handles³ \$115.00 (1)
 025SR2 Stroller Handle Regular ⁶ \$160.00 (1)
 025SR3 Stroller Handle Tall ⁶ \$160.00 (1)

FOOTNOTES:

- ¹ Seat width 1/2" narrower.
- ² Not available with adjustable upholstery.
- ³ Not available with Xtender.
- ⁴ Not available with adjustable upholstery.
- ⁵ Not available with push handles.
- ⁶ Not available with amputee axle plate or Xtender Power Assist.
- ⁷ Not available with fabric side guards.
- ⁸ Should additionally be billed as E0956.

NOTES:
 (1) OPTION FOR PURCHASE
 (2) JUSTIFICATION

CASTERS

<input type="checkbox"/>	025CW3	4" Low Profile Polyurethane	\$90.00	(1)
<input type="checkbox"/>	025CW31	4" Micro Light	\$90.00	(1)
<input type="checkbox"/>	025CW5	5" Low Profile Polyurethane	NC	
<input type="checkbox"/>	025CW7	5" x 1.5" Semi-Pneumatic ¹⁷	\$90.00	(1)
<input type="checkbox"/>	025CW6	5" Soft Roll Semi-Pneumatic	\$110.00	(1)
<input type="checkbox"/>	025CW33	6" Pneumatic	\$90.00	
<input type="checkbox"/>	025CW34	6" Polyurethane	NC	
<input type="checkbox"/>	025CW35	6" x 1.5" Semi-Pneumatic ¹⁷	\$90.00	
<input type="checkbox"/>	025CW21	8" Pneumatic	\$120.00	
<input type="checkbox"/>	025CW32	8" Polyurethane	NC	
<input type="checkbox"/>	025CW36	8" x 2" Pneumatic	\$205.00	(2)
<input type="checkbox"/>	025CW37	8" x 2" Pneumatic w/Airless Inserts	\$325.00	(2)

CASTER OPTIONS¹⁸

<input type="checkbox"/>	025CS5	3/4" Longer Stem Bolt	NC	
<input type="checkbox"/>	025CS9	1-1/2" Longer Stem Bolt	NC	
<input type="checkbox"/>	025CS6	WAMS Caster Pin Locks ¹⁸	\$124.00	(1)

ARMREST

<input type="checkbox"/>	025AA9	Height Adjustable Kids	\$280.00	
<input type="checkbox"/>	025AM1	Desk Length (10")	NC	
<input type="checkbox"/>	025AM2	Full Length (14")	NC	
<input type="checkbox"/>	025AA8	Height Adjustable Adult	\$280.00	
<input type="checkbox"/>	025AM1	Desk Length (10")	NC	
<input type="checkbox"/>	025AM2	Full Length (14")	NC	
<input type="checkbox"/>	025AA17	Padded SA Kids (12"-14" Deep) ¹⁸	\$260.00	
<input type="checkbox"/>	025AA19	Padded SA Medium (15 Deep) ¹⁸	\$260.00	
<input type="checkbox"/>	025AA16	Padded SA Adult (16"-22" Deep) ¹⁸	\$260.00	

FOOTREST

HANGER

<input type="checkbox"/>	025H1	60° Swing Away	NC	
<input type="checkbox"/>	025H2	70° Swing Away	NC	
<input type="checkbox"/>	025H6	90° Swing Away (Front Mount) ^{1,2}	NC	
<input type="checkbox"/>	025H24	Articulating ⁴	\$435.00	(1)
<input type="checkbox"/>	025H14	WAMK Elevating ⁵	\$280.00	(2)
<input type="checkbox"/>	025H32	Omit	-\$18.00	

FOOTPLATE

<input type="checkbox"/>	025F1	Composite w/Heel Loops 14"-20" ^{6,7}	NC	
<input type="checkbox"/>	025F3	WAMK Adult Angle Adj. w/Heel Loops	\$145.00	(2)
<input type="checkbox"/>	025F4	WAMK Kids Angle Adj. w/Leg Strap ⁹	NC	(2)
<input type="checkbox"/>	025F5	Aluminum ¹⁰	NC	
<input type="checkbox"/>	025F48	Platform Flip Up w/Leg Strap ¹²	\$190.00	(1)
<input type="checkbox"/>	025F7	Omit Footplate & Extension Tube	-\$18.00	

EXTENSION TUBE

<input type="checkbox"/>	025E1	Short (See chart for lengths) ^{7,13}	NC	
<input type="checkbox"/>	025E2	Medium (See chart for lengths)	NC	
<input type="checkbox"/>	025E5	Long (See chart for lengths)	NC	
<input type="checkbox"/>	025E14	Regular ELR	NC	
<input type="checkbox"/>	025E15	Long ELR	NC	
<input type="checkbox"/>	025E16	High Mount ^{14,15}	\$80.00	(2)

FOOTREST ACCESSORIES

<input type="checkbox"/>	025HL4	Omit Heel Loop	NC	
--------------------------	--------	----------------	----	--

IMPACT GUARD

<input type="checkbox"/>	025IG2	Neoprene ⁸	\$50.00	(1)
--------------------------	--------	-----------------------	---------	-----

Seat Sling to Top of Footplate Range

60° Swing-Away - Short Ext.	12 - 15 3/4
60° Swing-Away - Medium Ext.	14 1/2 - 18 1/4
60° Swing-Away - Long Ext.	17 - 20 3/4
60° Platform Flip-Up - Short	12 3/8 - 15 5/8
60° Platform Flip-Up - Medium	14 1/2 - 17 3/4
60° Platform Flip-Up - Long	17 - 20 1/4
70° Swing-Away - Short Ext.	11 - 14 3/4
70° Swing-Away - Medium Ext.	13 1/2 - 17 1/4
70° Swing Away - Long Ext.	16 - 19 3/4
70° Platform Flip-Up - Short	11 5/8 - 15 3/8
70° Platform Flip-Up - Medium	13 3/4 - 17 1/2
70° Platform Flip-Up - Long	16 1/4 - 20
70° "V" Swing-Away - Short Ext.	14 - 16 1/4
70° "V" Swing-Away - Medium Ext.	16 - 18 1/4
70° "V" Swing-Away - Long Ext.	18 - 20 1/4
70° "V" Platform Flip-Up - Short	12 3/8 - 15 1/8
70° "V" Platform Flip-Up - Medium	14 1/2 - 17 1/4
70° "V" Platform Flip-Up - Long	17 - 19 3/4

* All adjustment ranges may vary due to seat height restrictions. Recommended 2 1/2" footrest clearance to ground surface.

AXLE AND WHEEL

AXLE PLATE²⁴

<input type="checkbox"/>	025AL2	Standard Adjustable	NC	
<input type="checkbox"/>	025AL6	WAMT Amputee Adjustable ²²	\$120.00	(2)
<input type="checkbox"/>	025AL13	Double Slotted Adjustable	NC	

AXLE²⁴

<input type="checkbox"/>	025AX4	Quick Release Steel	NC	
<input type="checkbox"/>	025AX11	WAMU Quad Quick Release	\$150.00	(1)

FOOTNOTES:

- 1 Only available with kids angle adjustable, adult angle adjustable or 90° footboard footplates.
- 2 Extension tubes available, but must be ordered separately to ensure casters are cleared.
- 3 Only available with kids angle adjustable footplates.
- 4 Only available with composite and angle adjustable footplates.
- 5 Only available with aluminum or adult adjustable footplates.
- 6 Not available with 90° hangers and elevating legrest.
- 7 Not available with elevating legrests.
- 8 Only available on 60°, 70°, or 70°V hangers.
- 9 Only available on 12" - 16" width frames.
- 10 Only available with elevating hangers.
- 11 Only available on the 60°, 70° or 90° hangers.
- 12 Only available on the 60°, 70° or 70°V hangers.
- 13 Not available with articulating legrest.
- 14 Only available with adult angle adjustable or kids angle adjustable footplates.
- 15 Not available with elevating and 90° elevating legrests.
- 16 Available with adult angle adj. and kids angle adjustable footplates.
- 17 Only available in bottom fork hole.
- 18 Not available with Xtender Power Assist.
- 19 Not available with caster pin locks or with +3/4" or 1 1/2" fork stem bolt.
- 20 Not available with 8" x 2" casters.
- 21 NA with 12" wide. 13" wide only available with foam footplate. 14"-16" only available with foam or platform flip-up footplate. 17"-20" available with composite, foam, adult angle adjustable and platform flip up.
- 22 Not available with swing-away armrests.
- 23 Only available with Quickie Performance wheel options.
- 24 Not available with 8" x 2" casters or Xtender Power Assist.
- 25 Should additionally be billed as E0951.
- 26 Should additionally be billed as K0038.

NOTES:
(1) OPTION FOR PURCHASE
(2) JUSTIFICATION

REAR ANTI-TIP

<input type="checkbox"/>	025AT1	Rear Anti-Tip	\$100.00
--------------------------	--------	---------------	----------

REAR WHEEL

<input type="checkbox"/>	025RW8	22" Mag 14	NC
<input type="checkbox"/>	025RW9	22" Spoke 14	\$265.00
<input type="checkbox"/>	025RW1	24" Mag	NC
<input type="checkbox"/>	025RW2	24" Spoke	NC

REAR WHEEL TIRE

<input type="checkbox"/>	025RT1	Pneumatic18	NC
<input type="checkbox"/>	025RT2	Pneumatic Airless Insert ^{18,19}	\$205.00
<input type="checkbox"/>	025RT3	Full Polyurethane ^{1,2}	NC
<input type="checkbox"/>	025RT6	High-Pressure Clincher ^{4,5}	\$85.00 (1)

HANDRIM¹²

<input type="checkbox"/>	025HR1	Aluminum Anodized	NC
<input type="checkbox"/>	025HR4	WAMO Plastic Coated	\$130.00 (2)
<input type="checkbox"/>	025HR7	Omit Handrim	-\$24.00

PROJECTION HANDRIM

(Projections not available on plastic coated)

<input type="checkbox"/>	025HR8	WAMQ 8 Oblique ⁸	\$120.00
--------------------------	--------	-----------------------------	----------

GP Series Rear STF Chart

*All measurements given are an estimate and have been rounded to the nearest .5"

SHORT Frame (9 1/4" Front / 8 1/4" Rear)			Rear Axle Plate Hole Position					
Wheel	Rim	Tire	Standard			Inverted		
			Top	Middle	Bottom	Top	Middle	Bottom
22"	Mag / Spoke	Full Poly	14.5	15	15.5	16	16.5	17
22"	Mag / Spoke	Pneum / Insert	14.5	15	16	16	17	17.5
24"	Mag / Spoke	Full Poly	15	15.5	16.5	16.5	17	17.5
24"	Spoke / Spinerger	Clincher	15	16	16.5	16.5	17	18
24"	Mag / Spoke / Spinerger	Pneum / Insert	15.5	16	17	17	17.5	18
26"	Spoke / Spinerger	Clincher	16	17	17.5	17.5	18	19
26"	Spoke / Spinerger	Pneumatic	16.5	17	17.5	18	18.5	19

STANDARD Frame (10" Front / 9" Rear)			Rear Axle Plate Hole Position					
Wheel	Rim	Tire	Standard			Inverted		
			Top	Middle	Bottom	Top	Middle	Bottom
22"	Mag / Spoke	Full Poly	15	15.5	16.5	16.5	17.5	18
22"	Mag / Spoke	Pneum / Insert	15.5	16	17	17	17.5	18
24"	Mag / Spoke	Full Poly	16	16.5	17	17	18	18.5
24"	Spoke / Spinerger	Clincher	16	16.5	17	17.5	18	18.5
24"	Mag / Spoke / Spinerger	Pneum / Insert	16	16.5	17.5	17.5	18	18.5
26"	Spoke / Spinerger	Clincher	17	17.5	18	18.5	19	19.5
26"	Spoke / Spinerger	Pneumatic	17	18	18.5	18.5	19.5	20

FOOTNOTES:

- 1 Not available on 26" wheels.
- 2 Not available with Quickie Performance wheel options.
- 3 Only available on 24" rims.
- 4 Only available on 24" and 26" spoke rims.
- 5 Not available for heat treated rims.
- 6 Not available with heat-treated wheels.
- 7 Only available with 24" or 26" heat treated wheel rims.
- 8 Not available with 22" wheels.
- 9 Not available with polyurethane, latex tubular, turbo or high-pressure clincher tires.
- 10 Not available with grade aids or extension handles.
- 11 Not available with height adjustable armrests.
- 12 Not available with Xtender Power Assist.
- 13 Only available mounted to left side from rear
- 14 Not available with 8" x 2" casters or Xtender Power Assist.
- 15 Not available with swing-away armrests.
- 16 Only available with Quickie Performance wheel options.
- 17 Available with turbo tread or latex tubular tires; no charge.
- 18 Not available with Quickie Performance wheel options.
- 19 Not available on 26" wheels.

NOTES:
(1) OPTION FOR PURCHASE
(2) JUSTIFICATION

POSITIONING BELT

<input type="checkbox"/>	025A142	1.5" Auto Buckle	\$80.00
<input type="checkbox"/>	025A12	2" Aircraft Buckle	\$115.00 (1)
<input type="checkbox"/>	025A13	2" Aircraft Buckle Padded	\$170.00 (1)

SIDE GUARD

<input type="checkbox"/>	025SG4	WAMV Plastic Kids ¹¹	\$155.00 (1)
<input type="checkbox"/>	025SG3	WAMV Plastic Regular ¹¹	\$155.00 (1)

WHEEL LOCK

<input type="checkbox"/>	025WL1	High Mount Push	NC
<input type="checkbox"/>	025WL2	High Mount Pull	NC
<input type="checkbox"/>	025WL5	High Mount Scissor ¹⁰	NC
<input type="checkbox"/>	025WL12	Do Not Mount	NC
<input type="checkbox"/>	025WL10	Omit Wheel Lock	NC

GRADE AID

<input type="checkbox"/>	025GA1	WAMR Grade Aid ⁹	\$130.00 (1)
--------------------------	--------	-----------------------------	--------------

EXTENSION HANDLE¹²

<input type="checkbox"/>	025EH1	6" Pair	\$60.00
--------------------------	--------	---------	---------

TALL Frame (11" Front / 10" Rear)			Rear Axle Plate Hole Position					
Wheel	Rim	Tire	Standard			Inverted		
			Top	Middle	Bottom	Top	Middle	Bottom
22"	Mag / Spoke	Full Poly	16	16.5	17.5	17.5	18	19
22"	Mag / Spoke	Pneum / Insert	16.5	17	17.5	18	18.5	19
24"	Mag / Spoke	Full Poly	17	17.5	18	18.5	18.5	19.5
24"	Spoke / Spinerger	Clincher	17	17.5	18	18.5	19	19.5
24"	Mag / Spoke / Spinerger	Pneum / Insert	17	17.5	18.5	19	19	20
26"	Spoke / Spinerger	Clincher	18	18.5	19	19.5	20	20.5
26"	Spoke / Spinerger	Pneumatic	18	19	19.5	19.5	20	21

Maximum Dump 2 3/4"

*** Custom Frame Height Through Configurator - REAR 6 1/2 - 13" (Max frame squeeze = 3 1/2") Calculate Accordingly

GP Series Front STF Chart

*All measurements given are an estimate and have been rounded to the nearest .5"

SHORT Frame (9 1/4" Front / 8 1/4" Rear)										
Fork	Spacer	Fork Hole	3"	4" Poly	5" Poly	6" Poly	6" Pneu	8" Poly	8" Pneu	8x2
			4" Lighted	5" Soft Roll	6" x 1.5	6" x 1.5				
4 1/4	STD	Bottom	15.50	16.00	16.50	17.00	17.00	x	x	x
4 1/4	3/4	Bottom	16.50	17.00	17.00	17.50	18.00	x	x	x
4 1/4	1 1/2	Bottom	17.00	17.50	18.00	18.50	18.50	x	x	x
5 1/4	STD	Top	x	x	16.50	17.00	17.00	x	x	x
5 1/4	STD	Bottom	16.50	17.00	17.5	18.00	18.00	19.00	20.5	x
5 1/4	3/4	Top	x	x	17.50	18.00	18.00	x	x	x
5 1/4	3/4	Bottom	17.50	18.00	18.50	18.50	19.00	19.50	20.00	x
5 1/4	1 1/2	Top	x	x	18.00	18.50	18.50	x	x	x
5 1/4	1 1/2	Bottom	18.00	18.50	19.00	19.50	19.50	20.50	20.50	x
6	STD	Top	x	x	17.50	18.00	18.00	18.50	19.00	x
6	STD	Bottom	17.50	18.00	18.50	19.00	19.00	19.50	20.00	x
6	3/4	Top	x	x	18.00	18.50	18.50	19.50	19.50	x
6	3/4	Bottom	18.00	18.50	19.00	19.50	19.50	20.50	20.50	x
6	1 1/2	Top	x	x	19.00	19.50	19.50	20.50	20.50	x
6	1 1/2	Bottom	19.00	19.50	20.00	20.50	20.50	21.00	21.50	x
7	STD	Top	x	x	18.50	19.00	19.00	19.50	20.00	x
7	STD	Bottom	18.50	19.00	19.50	20.00	20.00	20.50	21.00	x
7	3/4	Top	x	x	19.00	19.50	19.50	20.50	20.50	x
7	3/4	Bottom	19.00	19.50	20.00	20.50	20.50	21.50	21.50	x
7	1 1/2	Top	x	x	20.00	20.50	20.50	21.00	21.50	x
7	1 1/2	Bottom	20.00	20.50	21.00	21.00	21.50	22.00	22.50	x
8x2	STD	Top	x	x	x	x	x	x	x	19.00
8x2	STD	Bottom	x	x	x	x	x	x	x	20.00
8x2	3/4	Top	x	x	x	x	x	x	x	19.50
8x2	3/4	Bottom	x	x	x	x	x	x	x	20.50
8x2	1 1/2	Top	x	x	x	x	x	x	x	20.50
8x2	1 1/2	Bottom	x	x	x	x	x	x	x	21.00

STANDARD Frame (10" Front / 9" Rear) ADD 3/4" to each measurement above

TALL Frame (11" Front / 10" Rear) ADD 1 3/4" to each measurement above

*** Custom Frame Height through Configurator - Front 9 - 13" - Calculate Accordingly (Minimum Front STF = 15 1/2" / Max = 26"